



Luvanto

Luxury Design Flooring

Luvanto Click & Click Herringbone

TECHNICAL INFORMATION



Characteristics	Test Method	Result
Level of Use	EN685	23, 32
Total Thickness	EN428	4.0mm
Wear Layer	EN429	0.5mm
Total Weight	EN430	8420g/m ²
Dimensions (Planks)	EN427	180mm x 1220mm
Dimensions (Sparkle)	EN427	149mm x 935mm
Dimensions (Tiles)	EN427	300mm x 600mm
Squareness and Straightness	EN427	≤0.07mm / ≤0.10mm
Surface Treatment		PU
Warranty		25 Years Domestic / 10 Years Commercial
Flammability	EN13501-1:2007	Bfl-S1
Abrasion Resistance	EN660-2	Wear Group P
Slip Resistance	DIN 51130	R10
Pendulum Test	BS7976-2:2002	Dry 62 (Low) / Wet 50 (Low)
Stain Resistance	EN423	Pass
Residual Indentation	EN433	0.02mm
Castor Chair Resistance	EN425	Pass
Colour Fastness to Light	ISO 105 B02	≥6
Curling	EN434	0.08mm
Shrinkage	EN434	≤0.25%
Flexibility	EN435	Pass
Sound Reduction	DIN52210	4dB
Underfloor Heating		Suitable, Max. 27°C