





Luvanto

Luxury Design Flooring

Luvanto Design & Design Herringbone

TECHNICAL INFORMATION



Produced to the following standards:
ISO 9001; ISO 14001; CE.

Characteristics	Test Method	Result
Level of Use	EN685	23.33
Total Thickness	EN428	2.5mm
Wear Layer	EN429	0.5mm
Total Weight	EN430	4400g/m ²
Dimensions (Planks)	EN427	152mm x 914mm / 184mm x 1219mm
Dimensions (Tiles)	EN427	305mm x 305mm / 305mm x 610mm
Squareness and Straightness	EN427	≤0.12mm / ≤0.15mm
Surface Treatment		PU
Warranty		25 Years Domestic / 10 Years Commercial
Flammability	EN13501-1:2007	Bfl-S1
Smoke Density	DIN4102	Class B1
Abrasion Resistance	EN660-2	Wear Group P
Slip Resistance	DIN 51130	R10
Pendulum Test	BS7976-2:2002	Dry 62 (Low) / Wet 50 (Low)
Stain Resistance	EN423	Pass
Residual Indentation	EN433	≤0.1mm
Castor Chair Resistance	EN425	Pass
Colour Fastness to Light	ISO 105 B02	≥6
Curling	EN434	≤2mm
Shrinkage	EN434	≤0.25%
Flexibility	EN435	20mm Mandrel No signs of cracking
Sound Reduction	DIN52210	4dB
Underfloor Heating		Suitable, Max 27°C